

ATTACHMENT B

UNDERGROUND UTILITIES INSTALLATIONS, MAINTENANCE AND REMOVALS

1. All underground utilities must be placed on the back 5 feet of the right-of-way of the declared county road except when written permission is granted by the chief administrative office of the county highway department.
2. All utilities placed in the county rights-of-way are to be placed a minimum of 36 inches deep and installed with tracer wire.
3. Utilities placed under paved county maintained roads will be placed by boring methods a minimum of 36 inches deep, cased with tracer wire.
4. Asphalt pavement shall not be cut for at least five (5) years following new paving and three (3) years following fresh chip seal.
5. Asphalt Cuts: All cuts must be approved by the CAO in writing; installed at a minimum depth of 36 inches, cased and tracer wire added.
6. Repair of Asphalt Cuts: Replaced with All virgin materials; 12 inch lifts compacted, 12 inches concrete or hot mix materials.
7. Utilities lines shall not be placed in drainage ditches, attached to bridges, culverts, tile, or other road structures, or ran through or over road drainage tile.
8. Natural Gas Utilities: All installation shall be outside the county declared rights-of-way. Written permission from the CAO must be obtained prior to installation of natural gas lines in the county rights-of-way. If approved by the CAO, installation shall be a minimum of 36 inches, cased with tracer wire.

ABOVE GROUND UTILITIES

1. Permitting not required for over-head utility installation and maintenance; however, if excavation is required a county permit must be obtained.
2. All utility markers, location and advertising signage located in the county rights-of-way must be maintained free of weed and brush within a 10 foot radius so said facility is easily visible. The county assumes no responsibility for any damage to any facility that is not properly maintained by the utility provider.